

# OFF-GRID INVERTER



## Output Data

### SNA 3000 WPV

### SNA 4000 WPV

### SNA 5000 WPV

Rated power	3000W/3000VA	4000W/4000VA	5000W/5000VA
Parallel capacity	YES	YES	YES
Normal output voltage	230/240, Split phase 220/110 Vac *	230/240, Split phase 220/110 Vac *	230/240, Split phase 220/110 Vac *
Normal output frequency	50/60Hz	50/60Hz	50/60Hz
Surge power	6000VA	8000VA	10000VA
Switch time	10ms	10ms	10ms
Waveform	Pure sine wave	Pure sine wave	Pure sine wave

## Battery Data

Battery Type	Lithium/Lead-Acid	Lithium/Lead-Acid	Lithium/Lead-Acid
Normal Voltage	51.2V/48V	51.2V/48V	51.2V/48V
Max. Charge Voltage	59V	59V	59V

## Solar Charger Data

Max. Recommended PV Power	6000W	6000W	6000W
MPPT Tracker	2	2	2
Max. PV Open Circuit Voltage	480Vdc	480Vdc	480Vdc
MPPT Voltage Range	100-385Vdc	100-385Vdc	100-385Vdc
Max. Solar Charge Current	100A	100A	100A
Max. MPPT Efficiency	>98%	>98%	>98%
Parallel MPPT Charger	YES	YES	YES

## AC Charger Data

Normal Voltage	230Vac	230Vac	230Vac
AC Voltage Range	110-280Vac	110-280Vac	110-280Vac
Max. Charge Current	60A	60A	60A
Frequency Range	50/60Hz(Auto Sensing)	50/60Hz(Auto Sensing)	50/60Hz(Auto Sensing)

## General Data

Dimensions(W/H/D)	504x330x135mm	504x330x135mm	504x330x135mm
Weight	14Kg	14Kg	14Kg
Protection Degree	IP 20	IP 20	IP 20
Relative Humidity	5%~95% Relative Humidity(Non-condensing)		
Operating Temperature	0~50°C	0~50°C	0~50°C
Storage Temperature	-15°C~60°C	-15°C~60°C	-15°C~60°C

## Interfaces

Display	LCD+LED	LCD+LED	LCD+LED
Lithium Battery Communication	CAN/RS485	CAN/RS485	CAN/RS485
RS485/Dry Connector	YES/YES	YES/YES	YES/YES
Wifi/GPRS	YES/YES	YES/YES	YES/YES
Warranty	2years	2years	2years

\* For split phase version